



FITTING GUIDE

Piranha Off Road Products are not associated in any way with Toyota Australia or any of its related companies

| DETAILS | |
|----------------------|-----------------|
| Part Number | BT78D10 |
| Approx. Fitting Time | 3 Hours |
| Max Battery Size | 2 x 265mm Long |
| Max Battery Weight | 2 x 21Kg |
| Battery Type | OPTIMA D34 Only |
| Tray Location | PSMT |

To Suit Landcruiser 78/79 Series HDJ78/79 Dual Cradle (Oil Filter Access)

Recommended Isolator
DBE140SF or DBE180-SX

| PARTS INCLUDED WITH TRAY | | | |
|--------------------------|--------------------|---|--------------------------|
| 1 | Tray | 5 | 6 x M8 Bolt Long |
| 2 | 1 x M6 Bolt | 6 | 2 x Universal Top Mounts |
| 3 | 1 x M6 Nut | 7 | 4 x J Bolts |
| 4 | 1 x M6 Body Washer | | |



Warning – Only to be used if a Triple Battery system is required & Use with BT78R

FITTING INSTRUCTIONS

1. Remove original battery & factory tray.
2. Reposition any wiring that is mounted where the new tray is to be fitted to the inner guard.
3. Relays on the top of inner guard will need to be re-positioned internally to the inner guard. Computer and glow plug solenoid need to be relocated.
4. Place tray into position and align the upper arms with holes in the inner guard. Use 3 x M8 bolts to secure.
5. Install 3 x M8 Bolts into wheel arch through the base of the tray
6. The M6 bolt, nut & washer are used for the forward most lower leg to bolt to the Wheel arch. **Note** – this may require drilling.

Please Note: It is the installers responsibility to check all items have adequate clearance and are secured/protected against vibration, rubbing & chaffing.

